

DECLARATION OF PERFORMANCE

No. CPR_01


1. Unique identification code of the product type: **Dry-pressed ceramic tiles, with water absorption Eb ≤ 0,5 %**
2. Intended uses: **For internal and external walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer: **Ceramiche Refin S.p.a, via 1° Maggio,22 – Salvaterra,4013 Casalgrande (RE) Italy.**
4. System(s) of assessment and verification of constancy of performance (AVCP): **System 4**
5. Name and identification number of notified laboratory, if relevant: **not relevant**
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	EN 14411:2015
Release of dangerous substance (only for GL ceramic tiles):		
- Cadmium	npd	
- Lead	npd	
Breaking strength (thickness ≥ 7,5)	≥ 1300 N	
Breaking strength (thickness < 7,5)	≥ 700 N	
Slipperiness	See table attached	
Tactility	npd	
Bond strength/adhesion	npd	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Arnold Stabinger
(Managing director)






Tabelle /Table
Scivolosità /Slipperiness /Glissancè
Rev.36 MARZO 2018

SERIE	SUPERFICIE	BCRA D.M. 236/1989
ARKE TIPO	NAT.	>40
ARTE PURA	NAT.	>40
ARTECH	NAT.	>40
ARTWORK	NAT.	>40
	OUT2	>40
AVANTGARDE	NAT.	>40
	BOCC.	>40
BAITA	NAT.	>40
BLUETECH	NAT.	>40
	OUT2	>40
BLUE EMOTION	NAT	>40
	OUT2	>40
BRICKLANE	NAT.	>40
CHEVRON	NAT.	>40
CONCRETE	NAT	>40
	OUT2	>40
CRAFT	NAT	>40
CROMIE	NAT.	>40
DECK	NAT.	>40
DESIGN INDUSTRY	NAT.	>40
	STRUTT.	>40
EPOQUE	NAT	>40
FABER	NAT	>40
FUSION	NAT	>40
GRAFFITI	NAT.	>40
	LAPP.	NPD
GRECALE	NAT	>40
HERITAGE	NAT.	>40
KASAI	NAT	>40
LARIX	NAT.	>40
	OUT2	>40
JARDINS	OUT2	>40
MANSION	NAT.	>40




Tabelle /Table
Scivolosità /Slipperiness /Glissancè
Rev.36 MARZO 2018

NORDIK	NAT.	>40
OVERLAY	NAT	>40
PETRAE	NAT	>40
	OUT2.	>40
PIERRES	OUT2	>40
PIETRE DI BORGOGNA	STRUTT.	>40
	STRUTT. OUT2	>40
	NAT.	>40
PLANT	NAT.	>40
	OUT2	>40
POESIA	NAT.	>40
	ANT.	>40
	OUT2	>40
PRESTIGIO	SOFT	>40
	LUCIDO	NPD
	LAPP.	NPD
TENAX	NAT.	>40
TRAIL	NAT.	>40
VELVET GROUND	NAT.	>40
VOYAGER	NAT	>40
WOOD2	NAT.	>40
	OUT2	>40
WIDE	NAT	>40
	STRUTT.	>40
	OUT2 STRUTT.	>40